

KBT



Security Solutions in Conveyor Belt Systems

Accessories of Security Solutions in Conveyor Belt Systems











The tow ropes are used in conveyor belt systems to control the switches

All connectors are designed for the KBT safety switch connection.

Within the European Union, these conditions are produced mainly DIN EN ISO 13850'den; EN / IEC 60 947-5-5 ve EN 620.

Connection Equipments

| Explanation | Product | Product | Order code |
|--|---|--|------------|
| 3mm steel rope 2mm isolated part total 5mm steel rope. |  | Steel rope | SR-050-03 |
| 4mm steel rope 2mm isolated part total 6mm steel rope |  | Steel rope | SR-060-03 |
| Eye and hook structure is made of galvanized It is used in the connection point of steel rope. |  | Eye hook Rigging screws galvanise | GK-10mm |
| Made of stainless steel, This spring draw steel rope and it uses during assembly. |  | Pull cord switch tension spring (stainless) | NB-055 |
| Made of galvanized material.This product steel rope is other equipment or for to chassis assemble. |  | Rope Connection accessory Klemens | ZB-216 |
| The product's rope which is stainless steel, uses to put it on parallel suspense. It can be used as connection accessory on connection points. It has M10 ring gear. |  | Pull cord Switch Carrying Hook (stainless) | KN-013 |
| 5mm bearing distance galvanized material is used to prevent the breaking of steel rope. |  | Thimble (galvanise) | RB-050 |
| 5mm bearing distance galvanized material is used to prevent the breaking of steel rope. |  | Thimble (galvanise) | RB-060 |



Connection Equipments

| Explanation | Product | Order code |
|---|----------------|------------|
| <p>1 This is a set of all the apparatuses required for the installation of a rope-cut switch.</p> <p>Contents</p> <p>1 Piece : Spring (NB-055)</p> <p>1 Piece : Pull Cord Switch Carrying Hook (Stainless) (KN-013) 1 Piece</p> <p>Eye Hook Rigging Screws galvanise (GK-10mm)</p> <p>2 Piece : Redans (RB-050)</p> <p>2 Piece : Klemens (ZB-216)</p> | Connection Set | YX19 |

Note : All products are used to assemble the wire rope and rope emergency stop switch in the conveyor belt line.
Installation may vary according to user preference.